

Heater Model 245



Free heat made possible with the **Horizon 245 single pass heater**, the perfect design for any shop. The multiple mounting systems allow for floor stand, tank rack or ceiling suspension mounting. Thanks to the accessible swinging door design near the chamber, up to 75% cleaning time is saved when compared to a conventional multi-pass system.

- Efficiency: The innovative Horizon Heater's heat exchanger design eliminates the costs of a burner target. This system also contains no fuel tubes, which means reduced cleaning time and no tube repair costs.
- Advanced Heat Exchanger Design: Reduces corners and thermal stress points to provide longer life and easier upkeep
- Warranty: lifetime limited heat exchanger warranty
- Dual Stack Connections: Vent gas out left or right side for a more versatile installation
- Dual, Multi-Directional Air Outlets: Left and/or right side, up or down, right or left louvering
- Squirrel Cage Blower Standard
- Light Weight: Easy to handle and install
- Multiple Voltages: 120-volt/60-amp and 220-volt/50-amp available
- Customized Heat Exchanger Cleanout Tool Standard: Promotes regular and complete maintenance of heat exchanger

SPECIFICATIONS

Input (approx. BTU/hr.)	245,000
Output (approx. BTU/hr.)	188,000
Stack size	8" / 20.3 cm
Shipping Weight	500 lbs./227 kg.
Heater dimensions (L x W x H)	41" x 26" x 99.5"
Includes outside measurements of fan and burner	
Duct Opening	18" x 18"
Electrical requirements (maximum circuit protection)	30A (15A for export)
Approx. fuel consumption	1.73 GPH
Blower CFM	2780
Outlet Air Temperature	180 F
Compressed air requirements	2 CFM @ 40 PSI / .057 m ³ /min.@.28Mpa
Agency listings	UL, C-UL

Patents

5,950,616

Fuels

Crankcase oil, transmission and hydraulic fluids, as well as other petroleum-based lubricants (any weight combinations up to SAE 50 as well as #1 and #2 fuel oil.)

Oil transfer pump

18 GPH @ 35 PSI (68 LPH @ .24 Mpa)